

OCEAN



FIELD TILES		
SIZE	SIZE SPECIFICATIONS	THICKNESS*
UNDULATED TILE		
3"x6"	2.913"x5.827" (74mm x 148mm)	0.307" (7.8mm)
3"x9"	2.913"x8.740" (74mm x 222mm)	0.319" (8.1mm)
DECORATIVE ACCESORIES & FINISHING TOUCHES		
Stripe Liner 0.8"x6"	0.787"x5.827" (20mm x 148mm)	0.472" (12mm)
Bar Liner 1"x6"	0.984"x5.866" (25mm x 149mm)	0.630" (16mm)
Quarter Round 1"x6"	0.984"x5.827" (25mm x 148mm)	0.354" (9mm)
Chair Molding 1.2"x6"	1.181"x5.866" (30mm x 149mm)	0.787" (20mm)
Rail Molding 2"x6"	1.968"x5.827" (50mm x 148mm)	0.945" (24mm)
Base Board (Glazed Top Edge) 6"x6"	5.866"x5.866" (149mm x 149mm)	0.551" (14mm)
APPLICATIONS		
	SUITABLE RESIDENTIAL	SUITABLE COMMERCIAL
Bathroom Walls**	YES	YES
Shower Walls**	YES	YES
Kitchen Walls**	YES	YES
Countertops	NO	NO
Fireplace Surrounds**	YES	YES
Outdoor Cooking / Bar Spaces (non-freeze - thaw climates)**	YES	YES
Pool Waterlines / Water Fountaines	NO	NO
Floors	NO	NO
PERFORMANCE CHARACTERISTICS		
	TEST METHOD ATSM / ISO	RESULT
Water Absorption	C-373 / 10545-3	Pass
Breaking Strength	C-648 / 10545-4	Pass
Chemical Resistance***	C-651 / 10545-14	Resistant
Facial Dimensions	C-499 / 10545-2	Pass
Range of Thickness	C-499 / 10545-2	Pass
Warpage	C-485 / 10545-2	Pass

OCEAN

INSTALLATION	
GROUT JOINT RECOMMENDATION	SHADE VARIATION
1/8"	V1 - Uniform Appearance

CLEANING RECOMMENDATIONS
Routine with a non-abrasive/non-acidic, mild and PH neutral cleaner
SEALING GUIDELINES
Solvent based penetrating sealer suitable for ceramic tiles

CHARACTERISTICS	
Glaze	Crackle with subtle movement
Surface Sheen	Glossy
Texture	Slightly Undulated

\*Thickness is understood as the highest point of the tile.  
\*\*Crackle tiles must be properly sealed. (See SEALING instructions in INSTALLATION & MAINTENANCE guidelines).  
\*\*\* In order to accomplish this test, the tile must be properly sealed.  
Due to the nature of our tile, a certain amount of variation in color, shading, surface and texture are to be expected.